



Piston Technical Data Sheet

QT-7.5

HP	7.5	cfm@175 psi	22.6
Low Pressure_Bor	4.5"	Pump Speed	1026
High Pressure_Bor	2.5"		
Stroke	3"	80 Gal V	80 Gal H
Max Working Pres	175	Dims (LxWxH)	37X24X74 70X23X74
Inlet Size	1" NPT	Weight	720 740
Air Outlet Size	3/4" BALL VALVE		
Min/Max RPM	500-1060 RPM		
Pump Life	50,000 HRS	Tank Pressure	200 psi
Duty Cycle	100%	Tank Fill Time	5.6 min
Lubrication	Quin-Cip		
Sump Capacity	1 qt. & 20 oz. (1.53 lit.)	Standard Warranty	Factory - 12 months parts / 12
Noise _dB(A)	79.7 ± 3	Extended Warr	3-Year Pump/ 2-Year Packa
Min operating_Temp	0 deg F	EWK part number	EWK-3
Max operating_Temp	104 deg F	EWK Contents	1 Air Filter, 6 qts Quin-Ciip D

*Duplex unit owners must purchase two (2) EWK kits
 *Engine-driven unit extended warranty is on air compressor only, "less engine". See engine manufacturer for warranty coverage.

Voltage:	120/1	230/1	200/3	230/3	460/3	575/3
Amp Draw:	-	40	25.3	22	11	9

*Applicable data doubled for Duplex models